

# ***HOLLYWOOD MOTORSPORTS***

## ***DEMOLITION DERBY ENTERTAINMENT, LLC 2019***

### ***STOCK MULTIPAL MINI RULES***

*(s10s, minie vans, small suvs,etc)*

## **VEHICLE PREPARATION**

**MANTITORY FULL FACE HELMETS WITH CHIN GUARD**

**NO CHRYSLER V BUMPERS NO V8'S**

Remove all glass, chrome, plastic, moldings, headliner, flammable material, A/C coolant, antifreeze, trailer hitches and interior decorating

Stock gas tank must be removed. A small metal tank must be mounted in the rear Seat area. The tank must be very secure and covered. Use proper rated fuel lines, Plastic tanks must be in a metal box. **NO EXCEPTIONS**

Electric fuel pump allowed but switch must be clearly marked on/off.

No more than (2) batteries allowed which must be relocated to front passenger Floor, secured and covered.

Floor shifter allowed. Ignition and wiring modifications (hotwire) allowed.

Hood must have 12" x 12" minimum hole to easily extinguish fires. Extra hole(s) in hood not required if header holes are least 12" x 12".

Car and driver qualify as a team for the feature.

**. 4 wheel and 2-wheel trucks and suv allowed. 4-wheel drive vehicles must remove one drive shaft.**

### **BUMPERS**

**1. You may change front bumper to 80 and newer, tube or pipe may be used. 3 x 4 max must be straight and hollow 3/8 max no creative bumpers allowed.**

**May be bolted or welded on to frame. Nothing welded past 4 inches from the front of the frame. NO EXCEPTIONS**

### **HOOD**

**1. Six bolts or six chains or six wires will be allowed. Two may go to frame, the other four may be sheet metal to sheet metal. If you choose to use threaded rod it must be welded vertically, one-inch max. Must be within 3 inches of stock location. Only one**

**of these three may be used.**

## ENGINE

1. Motors may interchange, must be within 4 inches of factory location. No v8s allowed  
Distributor protectors are not allowed transmission braces not allowed NO ENGINE  
CRADLES

## RADIATORS

1. Must be in stock location. No homemade radiators. No Radiator protectors allowed.  
No radi barrels

## DRIVER'S SAFETY

1. One bar in the dash is allowed. One bar behind the seat is allowed. If you choose you may connect these along the inside of door. Strongly recommended, only two down bars off back seat bar to the frame or body, vertical only. You may weld box to cab outside only two 8-inch straps per side. Minnie vans please weld your large doors if able. Dash bar must be 6 inches from trans hump. No cage material larger than 4x4 tube or pipe.

## DOORS

1. Doors may be chained, wired 2 spots per seam, or welded 5 on 5 off max ¼"x3" inch wide  
Strap. Nothing welded to frame. . Minnie vans please weld your large doors if able.

FENDERS 3 3/8 bolts per fender only

## FUEL

1. Fuel cell is highly recommended in a steel box. This is to be located in the most Forward center of box or inside of cab. Gas line to be run in a Protective conduit.

## TIRES

1. No ply restriction. Nothing higher than 30 inches tall.

## SUSPENSION

1. You may clamp springs, 4 per side. Clamp size, 7/16 bolts, 5 inch Length material 3 wide ¼ thick material. Max height 20 inches. Minimum frame height is 16 inches. No Homemade springs stock amount of factory springs for that vehicle. You may lightly weld front suspension down to get more height no larger than 1 inch material ¼ [no rod] thick vertical only Spring spacers allowed. Front upper and lower A arms must be stock like factory.

## BATTERIES

1. Two max, must be covered or in a box. All battery boxes and fuel cells must be securely Mounted.

## BODY BOLTS AND BOX

1. Body bolts leave them alone rusted or broken ones can be replaced. Box must remain upright in stock location, no tucking. No extra body bolts allowed.

STEERING. Must be stock steering. No modified tie rods. Aftermarket column allowed.

### **TAILGATE**

**1. Tailgate must remain upright in stock location. You have three ways of fastening your tailgate. You may wire or chain or weld a 3-inch-wide strap per seam. Outside only.**

### **AXELS**

- **Stock type rear-ends for that size and type of vehicles. Swapping rear ends is ok as long as it's a small truck or SUV type. (No full-size truck rear ends) You may chain your rear to frame one 3/8 chain per side.**

### **FRAME\***

**Repairs only allowed on a kinked area {not stressed}**

**4 inches by 3 inches by 1/4 total per frame rail when its gone to bad.**

### **WELDING**

**Nothing may be welded unless stated in the rules. This is your warning!**

**Otherwise**

**Prepare to stay on your trailer small repairs must call.**

### **SPIRIT OF THE RULE**

**Although every effort has been directed toward complete Understandable and correct rules as well as the same factors in**

**Putting them into print, Hollywood Motorsports cannot possible**

**Anticipate every situation, circumstance or interpretation.**

**With this in mind we must refer to the spirit of the rule.**

**ANY QUESTIONS CALL 9204102008**